

## AQUAFIL MASTIC FOR ROOFS

### USES

Aquafil mastic for roofs is multi-purpose trowel grade material for waterproofing, stopping, bedding, pointing and sealing. It can be applied to mastic asphalt, roofing felt, corrugated iron, cast iron, fibre cement, slates, lead, copper, zinc, concrete and timber. It dries to a flexible black material which remains soft and pliable for long time after application.

### PREPARATION

Ensure that the surface is clean, dry and free from loose material. If the surface is either dusty after cleaning, or covered with a weathered residue, prime with Aquafil Super Penetration Primer for roofs and allow to dry. To assist application in cold weather, store the material in a warm room overnight prior to use

### APPLICATION

Apply with a steel trowel or putty knife

**Cracks/holes:** Force Aquafil into the crack, covering the area to be treated by 25 MM either side, of the thickness of 3 MM. For large cracks and holes apply over areas to be treated and embed a closely woven glass fibre membrane into the compound to overlap the crack or hole by approx 50 MM. Allow to dry and then apply a second coat, fully covering the reinforced membrane.

**Corrugated iron/fibre cement sheeting:** Tighten loose hook bolts and trowel around the with Aquafil. Remove loose screws and washers in Aquafil and tighten; topseal and trowel to a smooth finish. If a sheet is cracked: clean, prime and apply a bandage with a strip of woven Glass membrane embedded in Aquafil. Allow to dry, then overcoat. Where it is required to seal side and end laps in corrugated sheeting use the same technique.

**Tiles:** Point up butt ends of ridge tiles, fillets and slates with Aquafil.

**Lead and zinc:** Trowel over cracks and pinholes, where necessary reinforcing with a fully embedded and covered woven Glass membrane.

**Felt:** Re-adhere loose felt especially flashings and details, and then seal joints with Aquafil.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

**Note:** Aquafil can only be applied to surfaces which are completely dry and great care must be taken to ensure that when applied to felt no moisture is contained within the felt.

### STORAGE

Up to 12 months in cool dry conditions in the temperature range 5°C to 35°C in an unopened container.

### HEALTH AND SAFETY

Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves/protective clothing/eye protection/face protection. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local regulations.