

WETGREASE

QUATTRO®

Wetgrease is a premium quality semi-synthetic water proof grease designed specifically for slow to medium speed plain and anti-friction bearing applications in marine and other hostile environments. Whilst it has found many uses for off road vehicles, due to its exceptionally high base fluid viscosity it is not recommended for normal highway use in automotive wheel and trailer hub bearings.

FEATURES

- Waterproof in both salt and fresh water.
- Good sealing properties to resist ingress of dirt and moisture.
- High load carrying capability.
- Reduces friction and wear.
- Highly adhesive to resist vibration and shock.

TYPICAL PHYSICAL CHARACTERISTICS

| | |
|---|-----------------------|
| Appearance | Green adhesive grease |
| Thickener | Lithium Soap |
| Base Oil | Semi – Synthetic |
| Worked penetration (IP50) | 265 to 295 |
| NLGI classification | 2 |
| Operating temperature range Deg C | 0 to + 140 |
| Dropping point (IP 132) kg | 180 min. |
| Timken O.K. load (IP326) kg | 25 |
| Dynamic corrosion SKF EMCOR with synthetic salt water | 0.1 |
| Water resistance (DIN 51807) | Fully resistant |
| Base Fluid viscosity (IP 71) cSt. @ 40 Deg | 1000 |

The content of this data sheet is given in good faith but without warranty.